

PP600H AC PowerPack

AC/DC Converter to Supply PS600 and PS1200HR Pump Systems with Backup Power from a Generator or Mains Supply

TECHNICAL DATA

- AC input: 120V or 240V ($\pm 15\%$), selectable, 47 to 63Hz
- AC input current: 6.2A (120V) or 3.1A (240V)
- PV input voltage: V_{mp} : 130V DC, depending on pump controller max. voltages
- PV max open circuit voltage: 200V DC depending on pump controller max. voltages
- DC output: 120V DC (no load), 700W
- Overload protection: internal fuse, 15A
- Enclosure: steel, gasket-sealed, indoor-use, hinged front cover with key-lock
- Must be protected from direct mid-day sun
- Enclosure class: IP22
- Ambient temperature: max. 45°C
- Manual with further informations is available in PartnerNet




WIRE SIZE

- All wires must be #14 AWG (2.5 mm²) or larger

STANDARDS

- Meets the requirements for CE



DIMENSION/WEIGHT

- Packing dimensions: 450 x 300 x 140 mm
17.7 x 11.8 x 5.5 in
- Total weight: 16kg / 35lbs

BERNT LORENTZ GmbH & Co. KG
Kroegerskoppel 7, 24558 Henstedt-Ulzburg, Germany,
Tel +49 (0)4193 7548-0, Fax -29, www.lorentz.de

Sun. Water. Life.

All specifications and information are given with good intent, errors are possible and products may be subject to change without notice. Pictures may differ from actual products depending on local market requirements and regulations.